



*NOTE: All relevant materials are complied with RoHS directive .

PIN ASSIGNMENT			
P1		P2	
1	_____	1	RED CONDUCTOR
6	_____	6	RED SHIELD
2	_____	2	GREEN CONDUCTOR
7	_____	7	GREEN SHIELD
3	_____	3	BLUE CONDUCTOR
8	_____	8	BLUE SHIELD
4	_____	4	BROWN
14	_____	14	BROWN/WHITE
5	_____	5	RED
12	_____	12	RED/WHITE
9	_____	9	YELLOW
10	_____	10	ORANGE
13	_____	13	ORANGE/WHITE
11	_____	11	BLACK
15	_____	15	BLACK/WHITE
SHIELD	_____	SHIELD	SHIELD

5	BLACK PVC TUBE $\varnothing 3.0 \times 22\text{mm}$	2	M304
	BLACK HEAT SHRINK TUBE $\varnothing 3.0 \times 10\text{mm}$	6	M743
	BLACK HEAT SHRINK TUBE $\varnothing 1.5 \times 10\text{mm}$	6	M743
	COPPER FOIL 33*65mm	2	M379
	MOLDED PE COLOR TRANSPARENT		TWN
	MOLDED PVC BLACK		M304
4	UL2919 {[28AWG+AL+S(29/0.10mmTS)]*3COAXIAL+(28AWG*4.5P)},AL+D+AMA BRAID(47%), OD:9.0mm, JACKET BLACK GROOVE, DRAWING No.EAAB2803T2804P2801C-197	L-20mm	M304
3	FERRITE CORE 17.5*10.5*28.5mm	2	M113
	MOLDED PVC BLACK		M304
2	MOLDED THUMBSCREW #4-40, LENGTH 48mm, BLACK	4	M95
1	HD15 MALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR	2	M108
No.	DESCRIPTION	Q'TY	Supplier
APPROVED		Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm	
CHECKED	TIAN		
DRAWING	XIANG		
DATE	28/DEC/07		
	ITEM NO.		
		UNIT:mm	